



GHS SAFETY DATA SHEET

300 PVC

Low VOC SOLVENT CEMENT FOR PVC PLASTIC PIPE

SECTION 1 – PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME: STRONG WELD 300 Low VOC Solvent Cement for PVC Plastic Pipe
SUPPLIER: HP INTERNATIONAL

PRODUCT USE: Solvent Cement for PVC Plastic Pipe
ADDRESS: G-11 Unique House, Chakala Road
Andheri (E) Mumbai 400099 INDIA
T: +91 22 2932 4739 F: +91 22 2834 9596

EMERGENCY: Transportation: CHEMTEL Tel. 800.255-3924, 813-248-0585 (International)

MEDICAL: Tel. 800.451.8346, 760.602.8703 3E Company (International)

SECTION 2 – HAZARDOUS IDENTIFICATION

GHS CLASSIFICATION:

Health
Acute Toxicity: Category 4
Skin Irritation: Category 3
Skin Sensitization: NO
Eye: Category 2
Environmental
Acute Toxicity: None Known
Chronic Toxicity: None Known
Physical
Flammable Liquid: Category 2



WHMIS CLASSIFICATION: CLASS B, DIVISION 2
CLASS D, DIVISION 1B

Hazard Statements

H225: Highly flammable liquid and vapor
H319: Causes serious eye irritation
H335: May cause respiratory irritation
H336: May cause drowsiness or dizziness
H351: Suspected of causing cancer
EUH019: May form explosive peroxides

Precautionary Statements

P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking
P261: Avoid breathing dust/fume/gas/mist/vapors/spray
P280: Wear protective gloves/protective clothing/eye protection/face protection
P337+P313: Get medical advice/attention
P403+P233: Store in a well ventilated place. Keep container tightly closed
P501: Dispose of contents/container in accordance with local regulation

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS	CAS#	EINECS #	REACH	CONCENTRATION
			Pre-registration Number	% by Weight
Tetrahydrofuran (THF)	109-99-9	203-726-8	05-2116297729-22-0000	10 – 30
Methyl Ethyl Ketone (MEK)	78-93-3	201-159-0	05-2116297728-24-0000	25 - 40
Cyclohexanone	108-94-1	203-631-1	05-2116297718-25-0000	20 - 30
Acetone	67-64-1	200-662-2	05-2116297713-35-0000	5 - 15

All of the constituents of this adhesive product are listed on the TSCA inventory of chemical substances maintained by the US EPA, or are exempt from that listing.
* Indicates this chemical is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372).
indicates that this chemical is found on Proposition 65's List of chemicals known to the State of California to cause cancer or reproductive toxicity.

SECTION 4 – FIRST AID MEASURES

Contact with eyes: Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately.
Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. If irritation develops, seek medical advice.
Inhalation: Remove to fresh air. If breathing is stopped, give artificial respiration. If breathing is difficult, give oxygen. Seek medical advice.
Ingestion: Rinse mouth with water. Give 1 or 2 glasses of water or milk to dilute. Do not induce vomiting. Seek medical advice immediately.
Likely Routes of Exposure: Inhalation, Eye and Skin Contact
Acute symptoms and effects:
Inhalation: Severe overexposure may result in nausea, dizziness, headache. Can cause drowsiness, irritation of eyes and nasal passages.
Eye Contact: Vapors slightly uncomfortable. Overexposure may result in severe eye injury with corneal or conjunctival inflammation on contact with the liquid.
Skin Contact: Liquid contact may remove natural skin oils resulting in skin irritation. Dermatitis may occur with prolonged contact.
Ingestion: May cause nausea, vomiting, diarrhea and mental sluggishness.
Chronic (long-term) effects: Category 2 Carcinogen

SECTION 5 – FIREFIGHTING MEASURES

Suitable Extinguishing Media: Dry chemical powder, carbon dioxide gas, foam, Halon, water fog.	HMIS	NFPA	0-Minimal
Unsuitable Extinguishing Media: Water spray or stream.	Health	2	2
Exposure Hazards: Inhalation and dermal contact	Flammability	3	3
Combustion Products: Oxides of carbon and smoke	Reactivity	0	0
Protection for Fire fighters: Self-contained breathing apparatus or full-face positive pressure airline masks.	PPE	B	4-Severe

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions: Keep away from heat, sparks and open flame. Provide sufficient ventilation, use explosion-proof exhaust ventilation equipment or wear suitable respiratory protective equipment. Prevent contact with skin or eyes (see section 8).
Environmental Precautions: Prevent product or liquids contaminated with product from entering sewers, drains, soil or open water course.
Methods for Cleaning up: Clean up with sand or other inert absorbent material. Transfer to a closable steel vessel.
Materials not to be used for clean up: Aluminium or plastic containers



+91-22-28324739



sales@hpint.in



www.hpint.in



HP International
11, Unique House, Chakala Rd,
Andheri (East), Mumbai - 400 099.



SECTION 7 – HANDLING AND STORAGE

Handling: Avoid breathing of vapor, avoid contact with eyes, skin and clothing. Keep away from ignition sources, use only electrically grounded handling equipment and ensure adequate ventilation/fume exhaust hoods. Do not eat, drink or smoke while handling.
Storage: Store in ventilated room or shade below 44°C (110°F) and away from direct sunlight. Keep away from ignition sources and incompatible materials: caustics, ammonia, inorganic acids, chlorinated compounds, strong oxidizers and isocyanates. Follow all precautionary information on container label, product bulletins and solvent cementing literature.

SECTION 8 - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

Table with 10 columns: Component, ACGIH TLV, ACGIH STEL, OSHA PEL, OSHA STEL, OSHA PEL-Ceiling, CAL/OSHA A PEL, CAL/OSHA Ceiling, CAL/OSHA A STEL. Rows include Tetrahydrofuran (THF), Methyl Ethyl Ketone (MEK), Cyclohexanone, and Acetone.

Engineering Controls: Use local exhaust as needed.
Monitoring: Maintain breathing zone airborne concentrations below exposure limits.
Personal Protective Equipment (PPE):
Eye Protection: Avoid contact with eyes, wear splash-proof chemical goggles, face shield, safety glasses (spectacles) with brow guards and side shields, etc. as may be appropriate for the exposure.
Skin Protection: Prevent contact with the skin as much as possible. Butyl rubber gloves should be used for frequent immersion. Use of solvent-resistant gloves or solvent-resistant barrier cream should provide adequate protection when normal adhesive application practices and procedures are used for making structural bonds.
Respiratory Protection: Prevent inhalation of the solvents. Use in a well-ventilated room. Open doors and/or windows to ensure airflow and air changes. Use local exhaust ventilation to remove airborne contaminants from employee breathing zone and to keep contaminants below levels listed above. With normal use, the Exposure Limit Value will not usually be reached. When limits approached, use respiratory protection equipment.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, regular syrupy liquid
Odor: Ketone
pH: Not Applicable
Melting/Freezing Point: -108.5°C (-163.3°F) Based on first melting component: THF
Boiling Point: 56°C (133°F) Based on first boiling component: Acetone
Flash Point: -20°C (-4°F) T.C.C. based on Acetone
Specific Gravity: 0.907 @23°C (73°F)
Solubility: Solvent portion soluble in water. Resin portion separates out.
Partition Coefficient n-octanol/water: Not Available
Auto-ignition Temperature: 321°C (610°F) based on THF
Decomposition Temperature: Not Applicable
VOC Content: When applied as directed, per SCAQMD Rule 1168, Test Method 316A, VOC content is: < 510 g/l.
Odor Threshold: 0.88 ppm (Cyclohexanone)
Boiling Range: 56°C (133°F) to 156°C (313°F)
Evaporation Rate: >1.0 (BUAC = 1)
Flammability: Category 2
Flammability Limits: LEL: 1.1% based on Cyclohexanone
UEL: 12.8% based on Acetone
Vapor Pressure: 190 mm Hg @ 20°C (68°F): Acetone
Vapor Density: > 2.0 (Air = 1)
Other Data: Viscosity: Regular bodied

SECTION 10 - STABILITY AND REACTIVITY

Stability: Stable
Hazardous decomposition products: None in normal use. When forced to burn, this product gives off oxides of carbon and smoke.
Conditions to avoid: Keep away from heat, sparks, open flame and other ignition sources.
Incompatible Materials: Oxidizers, strong acids and bases, amines, ammonia

SECTION 11 - TOXICOLOGICAL INFORMATION

Table with 4 columns: Toxicity, LD50, LC50, Target Organs. Rows include Tetrahydrofuran (THF), Methyl Ethyl Ketone (MEK), Cyclohexanone, and Acetone.

Table with 6 columns: Reproductive Effects, Teratogenicity, Mutagenicity, Embryotoxicity, Sensitization to Product, Synergistic Products. All entries are 'Not Established'.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: None Known
Mobility: In normal use, emission of volatile organic compounds (VOC's) to the air takes place, typically at a rate of < 510 g/l.
Degradability: Not readily biodegradable
Bioaccumulation: Minimal to none.

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Follow local and national regulations. Consult disposal expert.





GHS SAFETY DATA SHEET

300 PVC

Low VOC SOLVENT CEMENT FOR PVC PLASTIC PIPE

SECTION 14 - TRANSPORT INFORMATION

Proper Shipping Name: Adhesives
Hazard Class: 3
Secondary Risk: None
Identification Number: UN 1133
Packing Group: PG II
Label Required: Class 3 Flammable Liquid
Marine Pollutant: NO

EXCEPTION for Ground Shipping	
DOT Limited Quantity:	Up to 5L per inner packaging, 30 kg gross weight per package.
Consumer Commodity:	Depending on packaging, these quantities may qualify under DOT as "ORM-D".

TDG INFORMATION	
TDG CLASS:	FLAMMABLE LIQUID 3
SHIPPING NAME:	ADHESIVES
UN NUMBER/PACKING GROUP:	UN 1133, PG II

SECTION 15 - REGULATORY INFORMATION

Precautionary Label Information:	Highly Flammable, Irritant	Ingredient Listings: USA TSCA, Europe EINECS, Canada DSL, Australia AICS, Korea ECL/TCCL, Japan MITI (ENCS)
Symbols:	F, Xi	
Risk Phrases:	R11: Highly flammable. R36/37: Irritating to eyes and respiratory system.	R66: Repeated exposure may cause skin dryness or cracking R67: Vapors may cause drowsiness and dizziness
Safety Phrases:	S2: Keep out of the reach of children S9: Keep container in a well-ventilated place. S16: Keep away from sources of ignition. S25: Avoid contact with eyes.	S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S33: Take precautionary measures against static discharges.

SECTION 16 - OTHER INFORMATION

Specification Information:		
Department issuing data sheet:	HP INTERNATIONAL Quality Control	All ingredients are compliant with the requirements of the European Directive on RoHS (Restriction of Hazardous Substances).
E-mail address:	<qc@hpint.in>	
Training necessary:	Yes, training in practices and procedures contained in product literature.	
Reissue date / reason for reissue:	4/7/2015 / Updated GHS Standard Format	
Intended Use of Product:	Solvent Cement for PVC Plastic Pipe	

This product is intended for use by skilled individuals at their own risk. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.



+91-22-28324739



sales@hpint.in



www.hpint.in



HP International
11, Unique House, Chakala Rd,
Andheri (East), Mumbai - 400 099.